

NOTES:

VOLTAGE RANGE AC: 90-264VAC

OUTPUT VOLTAGE: 24VDC (22-28 ADJ)


AMP RATING: 0.68-0.54A

OUTPUT POWER: 15W

EFFICIENCY: 81%

OPERATING TEMP.: -10°C TO +50°C

FREQUENCY: 47-63Hz

| | | | | | |
|---|------|----------|--|-----------|----------|
| | NAME | DATE |  <p>Acme Electric[®] MENOMONEE FALLS, WI 53051 USA</p> | | |
| DRAWN | AJP | 11-21-17 | | | |
| CHECKED | AJP | 11-21-17 | | | |
| ENG APPR. | AJP | 11-21-17 | | | |
| <p>PROPRIETARY AND CONFIDENTIAL</p> <p>THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ACME ELECTRIC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF ACME ELECTRIC IS PROHIBITED.</p> <p>DO NOT SCALE DRAWING</p> | | | TITLE: PLASTIC | | |
| SCALE: 1:2 | | | SIZE | DWG. NO. | REV |
| SHEET 1 OF 1 | | | B | DMP124006 | A |