

Harmonic Mitigation Transformer - Three Phase, 480 Δ - 208Y/120V, 30kVA

By Acme Electric

Catalog ID: H3030K0014BS



* Representative image

By Acme Electric

Catalog ID: H3030K0014BS

Prop65_Cancer

Harmonic Mitigation Transformer - Three Phase, 480 Δ - 208Y/120V, 30kVA

Product Details

General

ANFC Taps	2
BNFC Taps	2
Construction	Ventilated
Electrostatic Shield	Shielded
Max Temperature Rise	150 Degrees Celsius
Mounting Type	Floor
Primary Voltage	480 Δ

Product Category	Harmonic Mitigation Transformer
Secondary Voltage	208Y/120 V
Taps % Steps	2.5%
UL Insulation Class	220°C
Winding Material	CU
kVA	30

Dimensions

Dimensions	22.37 in x 28.15 in x 29.9 in
Height	29.9 in
Length	22.37 in
Weight	360 lb
Width	28.15 in

Electrical Ratings

Efficiency	98.23%
Frequency Rating	60 Hz
Primary Voltage	480D V

Certifications and Compliance

CSA Standard

C22.2 No. 47

Dept of Energy Regulation

Meets or exceed U.S. DOE 10 CFR Part 431

Nema Rating

NEMA 3R

UL Standard

UL 1561
